

Road Cushion - (Austroad - AGTM08 -08 - Sect 7.2.2)

- Should generally be constructed 3.0 m long and 1.6 to 1.9 m wide with a height of 70-80mm.
- should have minimum gaps of 750 mm between the base of the cushions and kerb and also between adjacent cushions.

No. 7 Milray St

2 x Speed Cushions

2.1m - 2.3m Parking Lane

100m from  
LVG Driveway

No. 10 Milray St

**Preliminary Plan**

© Cardno Limited  
All Rights Reserved.  
This document is produced by Cardno Limited solely for the benefit of and use by the client in accordance with the terms of the retainer. Cardno Limited does not and shall not assume any responsibility or liability whatsoever to any third party arising out of any use or reliance by third party on the content of this document.



**Cardno**  
Shaping the Future

Cardno (NSW/ACT) Pty Ltd | ABN 95 001 145 035  
Level 9, The Forum, 203 Pacific Highway  
St. Leonards, NSW 2065  
Tel: 02 9496 7700 Fax: 02 9439 5170  
Web: [www.cardno.com.au](http://www.cardno.com.au)

Client	DEM Architects
Project	Lindfield Village Green Construction Certificate Requirements
Title	Milray Street Traffic Calming Speed Cushion Sheet 1 of 1 4/02/2019